

# Defender® Series

## Ballistic Rated Door

**Lietzke®**  
**ASSA ABLOY**



### Characteristics

- Full range of sizes
- Single or double-leaf version
- Integrated with a metal sub-frame
- Nominated thickness: 57mm
- Ballistic Performance: G0, G1, G2, R2



### Process

Built with a fully integrated steel sub-frame incorporating a 2.0 mm galvanised steel frame and supplied in a prime paint finish, engineered to deliver verified ballistic resistance and enhanced protection in high-risk environments.



### Hardware

- **Sub-Strata:** Bullet-resistant plate with steel sub-frame
- **Hinges:** Severe duty hinge
- **Lockset:** Lockwood secure area universal locking
- **Seal:** Standard door seal

Other configurable security hardware available upon request



### Finishing Options

- Supplied in prime paint, ready for final paint
- Powder Coated



### Door Frames

- 3-sided single rebate BW Frame
- 2mm thick GALVABOND® steel
- Supplied in prime paint, ready for final paint



### Standards and Compliance

- Tested and certified for G0, G1, G2, and R2 to AS 2343:1997 (Bullet-resistant panels and elements)

Defender® Series Ballistic Rated Door is a high-security, prehung steel door designed to protect personnel and property from armed threats, delivering verified ballistic resistance, enhanced security, and long-term performance in high-risk environments.

**Applications :** High-security sites requiring armed attack protection, such as police station and correctional facilities.

**Supply Options :** Doors supplied with specified steel frames



[www.lietzke.com.au](http://www.lietzke.com.au) Tel: 1800 lietzke

Ready to specify? Ask us for a [Specification Sheet](#).