

Defender® Series Door with 2point vertical locking

Lietzke

ASSA ABLOY

Technical Datasheet

⑥ Thickness



Hinge ⑦

⑤ Outer Panel

④ Core B

② Core A

① Inner Panel

TOP VIEW

⑪ Key and Lever with Cylinder

EXTERNAL VIEW

Enclosed Door Leaf Details:

- ① Inner Panel: 2mm Galvanised Steel Sheet
- ② Internal Core A: 25mm Hoop Pine Plywood
- ③ Optional Intermediate Panel: 3mm K700 Steel Plate
- ④ Internal Core B: 16mm Hoop Pine Plywood
- ⑤ Outer Panel: 2mm Galvanised Steel Sheet
- ⑥ Door Thickness: 45mm - 60mm (Customisable)

Door Furniture Details:

- ⑦ 4mm Continuous Hinge
- ⑧ Specified Lockset: Rivers Security Model DV Two-point Vertical Lock
*Rivers Security Four-point & Two-point Horizontal Lock available
- Optional Configurations:**
 - ⑨ Internal Handle
 - ⑩ Door Latch
 - ⑪ External Key and Lever with Cylinder

Finish Options:

- Supplied in **grey zinc rich primer**, ready for final paint

Defender® Series Door with 2point vertical locking is constructed with layered galvanized steel and equipped with high-security hardware. It operates inward or outward and is available in a full range of sizes in single or double-leaf configurations.

It can be installed in a 3 mm thick Zincanneal heavy-duty split frame design for full wall encapsulation.


The door is specified with a **Rivers Security Model DV Two-point Vertical Locking System**. Optional accessories include bullet-resistant vision panels, air relief grilles, eye viewers, door seals, and security hatches.

Engineered for **maximum protection and durability**, the door is ideal for both building perimeter and internal applications where the security of assets and property is critical.

Lietzke Australia PTY. LTD.

Adelaide Office: 25 Circuit Court, Hendon SA 5014
Brisbane Office: 181-185 Cobalt St, Carole Park, QLD 4300
Email: sasales@lietzkesecurity.com.au
qldsales@lietzkesecurity.com.au
Phone: (08) 8445 9999 Fax: (08) 8347 2073

DO NOT SCALE DRAWING. DIMENSIONS IN MILLIMETERS.



GENERAL TOLERANCES:

Unless Otherwise Stated:
0 Dec. place $\pm 0.5\text{mm}$
1 Dec. place $\pm 0.25\text{mm}$
2 Dec. place $\pm 0.10\text{mm}$
Holes: $+0.25\text{mm}$ -0mm
Angles: $\pm 0.25^\circ$