

# Defender® Series Secure Glazed Door

## Technical Datasheet



### Pre-hung Door Set:

- Glazing door with RHS frame
- Size: Maximum - 2170 x 2722 mm
- Thickness: 50mm (nominal)
- Certified water resistance: up to 400 Pa
- Tested in accordance with AS2047-2014

- ① Door Leaf (Single/Double configuration)

### Components Details:

- ② Hinge: Heavy-duty ball bearing hinge
- ③ Lockset: Lockwood Electric Mortice Lock
- ④ Glazing: 8.38mm thick clear laminated glass

Other configurable security hardware available upon request

### Pre-hung Door Frame:

- ⑤ Door frame:
  - 3-sided single rebate BW Frame
  - 2mm thick GALVABOND® steel
  - Supplied in prime paint, ready for final paint
- ⑥ Seal: Pre-prepped perimeter seal

### Finish Options:

- Supplied in prime paint, ready for final paint
- Powder Coated

Defender® Series Secure Glazed Door is a heavy-duty glazed door designed to resist weather ingress while enhancing building security, comfort, and long-term performance.


It is supplied with a pre-hung specified steel frame filled with pre-prepped perimeter seal.

Tested to AS2047-2014, it delivers reliable performance for commercial or industrial buildings where a secure glazed door is required to resist weather ingress and maintain internal comfort and building performance.

#### Lietzke Australia PTY. LTD.

Adelaide Office: 25 Circuit Court, Hendon SA 5014  
 Brisbane Office: 181-185 Cobalt St, Carole Park, QLD 4300  
 Email: sasales@lietzkesecurity.com.au  
 qldsales@lietzkesecurity.com.au  
 Phone: (08) 8445 9999 Fax: (08) 8347 2073

DO NOT SCALE DRAWING.  
 DIMENSIONS IN MILLIMETERS.



#### GENERAL TOLERANCES:

Unless Otherwise Stated:  
 0 Dec. place  $\pm 0.5$ mm  
 1 Dec. place  $\pm 0.25$ mm  
 2 Dec. place  $\pm 0.10$ mm  
 Holes:  $+0.25$ mm  $-0$ mm  
 Angles:  $\pm 0.25^\circ$

Scan for more information

