

# Flange Fit

## Door Frames Series



Flange Fit Frame - Split Frame

Lietzke Flange Fit Frame Series is designed for **fast and efficient installation into prepared openings**. The integrated flange conceals wall edges, while factory pre-hung doors ensure accurate operation and installation.

**Applications:** Commercial, industrial, and retrofit openings requiring quick installation and a neat finished edge

**Supply Options:**

- Pre-hung unit - Door installed in the frame
- Frame only



[www.lietzke.com.au](http://www.lietzke.com.au) Tel: 1800 lietzke

Ready to specify? Ask us for a [Specification Sheet](#).



### Characteristics

- Full range of sizes to match door leaf
- 1.2mm & 1.6mm ZF100 Zincanneal for standard material
- Flange conceals wall opening edges
- Operation and clearances pre-checked



### Process

Factory pre-hung and precision-aligned, featuring a flange-fit design that conceals wall edges for a fast, clean, and low-adjustment installation - ensuring reliable performance, minimal site work, and a professional finish.



### Construction

- **Fabrication:** Joints are precision-notched, welded, and ground flush - including mitred joins on split frames
- **Edge Style:** Face sheets return on all sides, with overlapping edges secured by countersunk rivets



### Frame Options

- **Three-sided Frame:** Ideal for inward-opening & outward opening doors; handing must be specified.
- **Four-sided Frame:** Reversible installation with added rigidity and sealing.
- **Split Frame:** Two-part frame for secure, dual-sided installation.



### Finishing Options

- Supplied in standard Colorbond colour with factory-applied durable polyester Powdercoat, optional colours available
- Prime paint - Optional
- Also offered in 304 or 316 Grade Stainless Steel.
- Other options available upon request.