

Heavy-duty Chevron Louvre Door Series



Characteristics

- Full range of sizes
- Single or double-leaf version
- The material shown is adaptable to standard steel doors and frames
- Various mesh options are available for installation with louvres
- Edge Style available in Rebate Edge for maximum RW rating or Squareline Edge for lower ratings



Process

Constructed with a welded 1.6mm SHS steel sub-frame and 1.2mm Galvabond® louvre blades, sealed with rivets for moisture resistance and finished for durability in high-demand environments.



Blade Type



Chevron Louvre Blade



Finishing Options

- Supplied in standard Colorbond colour with factory-applied durable polyester Powdercoat, optional colours available.
- Also offered in 304 or 316 Grade Stainless Steel.
- Other options available upon request.



Door Frames

- 1.6mm thick pressed metal
- Available in 3-sided or 4-sided design
- Zinc Rich Primer or Powder coated for corrosion resistance
- Available options: BW Frame/ Single Frame/ Double Frame/ Split Frame

Lietzke Heavy Duty Chevron Louvre Door Series is a **robust, steel-framed pre-hung door** providing **moderate airflow, enhanced security, and a non-transparent barrier** for asset protection.

Applications: Substations, data centres, and plant rooms requiring moderate airflow and privacy.

Supply Options:

- Pre-hung unit - Door installed in the frame
- Door leaf only



www.lietzke.com.au Tel: 1800 lietzke

Ready to specify? Ask us for a **Specification Sheet**.