

Defender[®] Series

Secure Glazed Door

Lietzke[®]
ASSA ABLOY



Characteristics

- Glazing door with RHS frame
- Maximum size: 2170 x 2722mm (Length x Width)
- Single or double-leaf version
- Nominated thickness: 50mm
- Nominated Glazing: 8.38mm thick clear laminated glass



Process

Built with a fully integrated RHS steel frame and 2.0 mm Galvabond[®] rebate construction, fitted with 8.38 mm clear laminated glass and supplied in prime paint finish, engineered to minimise perimeter gaps and providing a high ultimate strength and resistance to air and water penetration.



Hardware

- **Hinge:** Heavy-duty ball bearing hinge
- **Lockset:** Lockwood Electric Mortice Lock
- **Seal:** Pre-prepped perimeter seal

Other configurable security hardware available upon request



Finishing Options

- Supplied in prime paint, ready for final paint
- Powder Coated



Door Frames

- 3-sided single rebate BW Frame
- 2mm thick GALVABOND[®] steel
- Supplied in prime paint, ready for final paint



Standards and Compliance

- Tested in accordance with AS2047-2014 (Windows and external glazed doors in buildings)
- Certified water resistance: up to 400 Pa

Defender[®] Series Secure Glazed Door is a heavy-duty glazed door designed to resist weather ingress while enhancing building security, comfort, and long-term performance.

Applications: Commercial or industrial buildings where a secure glazed door is required to resist weather ingress and maintain internal comfort and building performance.

Supply Options: Doors supplied with specified steel frames



www.lietzke.com.au Tel: 1800 lietzke

Ready to specify? Ask us for a [Specification Sheet](#).