

Security 1

Door Series

Lietzke®
ASSA ABLOY



Characteristics

- Full range of sizes
- Single or double-leaf version
- Supplied with durable SHS steel sub-frame
- Optional anti-jemmy edge and configurable hardware
- The adaptability of the material shown to standard steel doors and frames



Process

Constructed with a rigid core and Colorbond® steel, the door features a galvanised SHS steel sub-frame for enhanced strength, with optional anti-jemmy edges for a secure, clean, and professional finish.



Internal Core Options

Security 1 Metal Clad **Rigid Foam Core** Door

- Rigid Polystyrene Solution
- Polyisocyanurate (PIR) Solution

Security 1 Metal Clad **Solid Core** Door

- Blockboard Solution
- Particleboard MDF Solution
- Marine Grade Plywood Solution



Finishing Options

- Supplied in standard Colorbond colour with factory-applied durable polyester Powdercoat, optional colours available
- Also offered in 304 or 316 Grade Stainless Steel.
- Other options available upon request.



Door Frames

- 1.6mm thick pressed metal
- Durable powder-coated finish
- Available in 3-sided or 4-sided design
- Available options: BW Frame/ Single Frame/ Double Frame/ Split Frame

Lietzke Security 1 Door Series is a **robust, steel-reinforced pre-hung door with an SHS steel sub-frame** for high strength, stability and secure access.

Applications : Commercial, industrial, and public facility for both internal and external security use

Supply Options :

- Pre-hung unit - Door installed in the frame
- Door leaf only



www.lietzke.com.au Tel: 1800 lietzke

Ready to specify? Ask us for a [Specification Sheet](#).