

Security 2

Door Series



Characteristics

- Full range of sizes
- Single or double-leaf version
- Supplied with durable SHS steel sub-frame with 2 inner vertical SHS sections
- Optional anti-jemmy edge and configurable hardware
- The adaptability of the material shown to standard steel doors and frames



Process

Built with a solid timber core, encased in pre-painted Colorbond® steel and reinforced with a galvanised SHS steel frame on all edges and the middle of the door for a clean, secure, and impact-resistant finish.



Internal Core Options

Security 2 Metal Clad **Solid Timber Core** Door

- Timber Blockboard Solution
- Particleboard MDF Solution
- Marine Grade Plywood Solution

Security 2 Metal Clad **Rigid Foam Core** Door

- Rigid Polystyrene Solution
- Polyisocyanurate (PIR) Solution



Finishing Options

- Supplied in standard Colorbond colour with factory-applied durable polyester Powdercoat, optional colours available
- Also offered in 304 or 316 Grade Stainless Steel.
- Other options available upon request.



Door Frames

- 1.6mm thick pressed metal
- Durable powder-coated finish
- Available in 3-sided or 4-sided design
- Available options: BW Frame/ Single Frame/ Double Frame/ Split Frame

Lietzke Security 2 Door Series is a **high-strength, impact-resistant pre-hung door featuring a galvanised SHS steel sub-frame** for high-risk commercial, industrial, and remote environments.

Applications : Financial, government, defence, commercial, and industrial sectors requiring high security

Supply Options :

- Pre-hung unit - Door installed in the frame
- Door leaf only



www.lietzke.com.au Tel: 1800 lietzke

Ready to specify? Ask us for a **Specification Sheet**.